



GATA KATU	ÖVERBYGGNAD																								
	AVSTÅND																								
	170,72																								
	-0,008																								
	LUTNING / RADIE																								
	BALANSLINJENS HÖJD																								
	TASAUUSVIIVAN KORKEUS																								
	6,29	6,21	6,14	6,06	5,98	5,90	5,82	5,75	5,67	5,59	5,51	5,43	5,36	5,28	5,20	5,12	5,04	4,97	4,96	5,01	5,06	5,11	5,17	5,22	5,26

MARKKYTÄ MAANPINTA	MARKKYTÄNS HÖJD MAANPINNAN KORKEUS
0	5,84
50	5,71
100	5,93
150	5,66
200	5,79
250	5,69
300	5,98
350	5,54
400	5,47
450	5,93
500	5,26
550	4,97
600	5,16
650	6,16
700	6,14
750	6,35
800	5,17
850	5,51
900	5,69
950	5,93
1000	6,18
1050	5,60
1100	6,06

[illegible]

[illegible]

Technical drawing of a road cross-section. The drawing shows a road with a width of 10m and a central area of 4.50m. The side slopes are 5% and the central area is 4.50m wide. The drawing includes a green profile line, a black centerline, and a table of dimensions.

AB	50mm
H	0-32
H	0-100
L-Sign	300mm
Total	750mm

[illegible]